

# Cement Transport Truck Mercedes Actros 47m Diesel Pump Concrete Boom Pump Truck

# **Basic Information**

Place of Origin: China
Brand Name: Pump Truck
Minimum Order Quantity: 1 Unit

• Price: 110,000.00/units =1 unit

Delivery Time: 10-20work days
Payment Terms: L/C, D/A, D/P, T/T

• Supply Ability: 100 units



# **Product Specification**

Chassis Brand: Shacman Sinotruck North Rush Heavy

Truck, Dongfeng, Isuzu, Auman

Emission Standard: Euro -Euro
Engine Horsepower: 240-470HP
Drive Type: 4X2、6X4、8X4

• Turn Table Rotation Angle: 359°

• Maximum Theoretical 110-180(m³/h)

Concrete Pumping Volume:

• Tyre: 11.00R20,12.00R20,12R22.5,295/80R22.5,315/80R22.5

• Cab: Flat Top/Low Top/High Top

Air Conditioner: ManualABS(Antilock Braking Yes

System):

• ESC(Electronic Stability None

Control System):

Seat Rows: Single Row

### **Product Description**

There are both brand new and second-hand trucks. Just tell us your transportation needs and we will customize tractors with different loading weights, volumes, and colors. A good truck will help you work well.

#### **Product Description OF Concrete Pump Truck:**

The supporting floor must be level. Otherwise it will be necessary to make a horizontal bearing surface. Cannot be supported on holes. The pump truck must be supported on a solid ground. If the maximum pressure of the outriggers is greater than the allowable pressure on the ground, a support plate or auxiliary square wood must be used to increase the support surface area.

When the pump truck is supported near a pit or slope, sufficient safety distance should be maintained.

When supporting, it must be ensured that the whole machine is in a horizontal state, and the maximum horizontal deflection angle of the whole machine in the front, rear, left, and right does not exceed 3 degrees.

When unfolding or retracting the outriggers, the rotating range of the outriggers is a dangerous area, and people may be pinched within the range.

When supporting, all outriggers must telescope and unfold to the specified position (the arrows on the outriggers are aligned with the support ears, and the arrows on the front outrigger arms are aligned with the arrows on the front outrigger arms), otherwise there is a risk of overturning. The outriggers must be supported as required before the boom can be operated. The outriggers must be retracted and placed on the main support of the boom before the outriggers can be retracted. If factors that reduce stability occur, the boom must be retracted immediately. After elimination, the boom must be supported again as required to reduce the risk. Stability factors include changes in ground conditions caused by rain, snow, or other water sources.

#### **Product Application OF Concrete Pump Truck:**

At present, the main products include 28m, 31m, 33m, 38m, 50m, 58m, and 65m concrete pump trucks and 28m, 38m, 44m, and 46m mixing pump trucks, 24m, 36m, and 47m aerial work vehicles, 10-50 ton bulk cement trucks, mobile unloadable mixing stations and other engineering machinery equipment; the country's first two-axle 38m pump truck, 46m mixing pump truck, four-axle 65m pump truck, cement truck, mobile unloadable mixing station and other star products.

Dedicated to serving urban and rural infrastructure, it is an enterprise specializing in the production of large-scale construction engineering machinery and equipment, integrating scientific research, production, sales and after-sales service.

#### **Product Features OF Concrete Pump Truck:**

Product Name	Concrete Pump Truck 4X2/6X4/8X4
Wheelbase	1950+4650+1350 mm
Engine Model	WEICHAI/Commins
Horsepower	240-470 horsepower
Vehicle Quality	18000-47000kg
Bridge Number	4
Tyre	11.00R20,12.00R20,12R22.5,295/80R22.5,315/80R22.5
Colour	As customer's request
MAX pumping Capacity	180m³
Provide After-sales Service	Video technical support, online support

▲ The values in the configuration table are subjected to change. The data in the configuration table are for reference only. Mix and matching some configurations may not be technically possible, please contact your local sales representative to help you choose the right specifications for your needs.

#### **Product Image**







# 1.Q: What kind of payment do you accept?

A: We accept T/T;L/C and Western Union; Others payment is negotiable.

2.Q: What's your minimum order quantity?

A: One unit

3.Q: What's your delivery time?

A:Determine according to the specirie Moael. dump truck usually 30 days after received the deposit.

4.Q: What's warranty time?

A: 30,000 km or 12 months from the date of shipment whichever comes firs

5.Q: What's your after-sale service?

A: We provide technical support for our trucks and whole life parts supply

Hot Tags: Pump truck 8x4 6x4 4x2, China, suppliers, concrete pump truck, price, best, brand new, for sale



# Zhengzhou Hongyang Automobile Sales Service Co., Ltd.



13629843569



celia@zzhonyang.cn



chinadumptrucks.com